



Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.09.2015

Version number 2

Revision: 04.09.2015

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

- **1.1 Product identifier**
- **Trade name: CONTI SECUR BFA WEISS**
- **Article number: 114013.BULK.00**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
- **Product category PC1 Adhesives, sealants**
- **Application of the substance / the mixture Adhesives**
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
H.B. Fuller, Isar-Rakoll, S.A.
Estrada Nacional 13
PT-4486-851 Mindelo - Vila do Conde
+351 229 288 200
EU-MSDS@hbfuller.com
- **Informing department: Regulatory Department**
- **1.4 Emergency telephone number:**
NCEC emergency service
+44 (0) 1235 239 670 (24 hours)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Flam. Liq. 2 H225 Highly flammable liquid and vapour.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.
Aquatic Acute 1 H400 Very toxic to aquatic life.
Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the CLP regulation.
- **Hazard pictograms**



GHS02 GHS07 GHS09

- **Signal word** Danger
- **Hazard-determining components of labelling:**
ethyl acetate
cyclohexane
- **Hazard statements**
H225 Highly flammable liquid and vapour.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H410 Very toxic to aquatic life with long lasting effects.

(Contd. on page 2)

GB

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.09.2015

Version number 2

Revision: 04.09.2015

Trade name: **CONTI SECUR BFA WEISS**

(Contd. of page 1)

- **Precautionary statements**

- P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting/equipment.
- P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Additional information:**

Contains Rosin. May produce an allergic reaction.

- **2.3 Other hazards**

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Chemical characterisation: Mixtures**

- **Description:** Adhesive.

- **Dangerous components:**

CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-0000	ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	25-50%
CAS: 110-82-7 EINECS: 203-806-2 Reg.nr.: 01-2119486291-36-0000	cyclohexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336	25-50%
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-0000	acetone Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	5-10%
CAS: 31394-54-4 EINECS: 250-610-8	isoheptane Flam. Liq. 1, H224; Asp. Tox. 1, H304; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Irrit. 2, H315; STOT SE 3, H336	<5%
	2-methylpentane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	<5%
CAS: 110-54-3 EINECS: 203-777-6	n-hexane Flam. Liq. 2, H225; Repr. 2, H361f; STOT RE 2, H373; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336	<2.5%
CAS: 1314-13-2 EINECS: 215-222-5	zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410	0.5-1%
CAS: 8052-10-6 EINECS: 232-484-6	Rosin Skin Sens. 1, H317	0.5-1%

- **Additional information** For the wording of the listed risk phrases refer to section 16.

GB

(Contd. on page 3)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.09.2015

Version number 2

Revision: 04.09.2015

Trade name: **CONTI SECUR BFA WEISS**

(Contd. of page 2)

SECTION 4: First aid measures

- **4.1 Description of first aid measures**
- **General information**
Instantly remove any clothing soiled by the product.
Take affected persons into the open air.
- **After inhalation** Supply fresh air; consult doctor in case of symptoms.
- **After skin contact** Instantly wash with water and soap and rinse thoroughly.
- **After eye contact** Rinse opened eye for several minutes under running water. Then consult doctor.
- **After swallowing** Do not induce vomiting; instantly call for medical help.
- **4.2 Most important symptoms and effects, both acute and delayed**
Headache
Disziness
Coughing
Disorientation
- **4.3 Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

SECTION 5: Firefighting measures

- **5.1 Extinguishing media**
- **Suitable extinguishing agents**
CO₂, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.
- **For safety reasons unsuitable extinguishing agents** Water with a full water jet.
- **5.2 Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **5.3 Advice for firefighters**
- **Protective equipment:** Do not inhale explosion gases or combustion gases.
- **Additional information**
Cool endangered containers with water spray jet.
Collect contaminated fire fighting water separately. It must not enter drains.
Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Keep away from ignition sources
Wear protective clothing.
- **6.2 Environmental precautions:**
Do not allow to enter drainage system, surface or ground water.
Inform respective authorities in case product reaches water or sewage system.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
Send for recovery or disposal in suitable containers.
Do not use tools that can cause ignition.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.

(Contd. on page 4)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.09.2015

Version number 2

Revision: 04.09.2015

Trade name: CONTI SECUR BFA WEISS

(Contd. of page 3)

See Section 13 for information on disposal.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Store in cool, dry place in tightly closed containers.
 Ensure good ventilation/exhaustion at the workplace.
 Prevent formation of aerosols.
 Take note of emission threshold.
 Use solvent-proof equipment.
 Keep out of the reach of children.

Information about protection against explosions and fires:



Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.
 Highly volatile, flammable constituents are released during processing.
 Fumes can combine with air to form an explosive mixture.
 Flammable mixtures may be formed in empty containers.

7.2 Conditions for safe storage, including any incompatibilities

Storage

Requirements to be met by storerooms and containers: Provide solvent resistant, sealed floor.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Protect from heat and direct sunlight.
 Store in cool, dry conditions in original sealed container

Recommended storage temperature: +10 °C - +25 °C

7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

8.1 Control parameters

Components with limit values that require monitoring at the workplace:

141-78-6 ethyl acetate

WEL	Short-term value: 400 ppm Long-term value: 200 ppm
-----	---

67-64-1 acetone

WEL	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
-----	--

DNELs

Ethylacetat, CAS 141-78-6 (Arbeitnehmer)
 dermal Langzeit(chronisch) systemisch: 63 mg/kg/Tag
 inhalativ Kurzzeit (akut) systemisch: 1468 mg/m³
 inhalativ Langzeit(chronisch) lokal: 734 mg/m³
 inhalativ Kurzzeit (akut) lokal: 1468 mg/m³
 inhalativ Langzeit (chronisch) systemisch: 734mg/m³

Cyclohexan CAS 110-82-7

Langzeit-Exposition - systemische Effekte:

(Contd. on page 5)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.09.2015

Version number 2

Revision: 04.09.2015

Trade name: CONTI SECUR BFA WEISS

(Contd. of page 4)

Dermal DNEL 2016 mg/kg (Arbeiter)
 Inhalativ DNEL 700 mg/m³ (Arbeiter)
 Langzeit-Exposition - lokale Effekte:
 Inhalativ DNEL 700 mg/m³ (Arbeiter)
 Kurzzeit-Exposition - systemische Effekte:
 Inhalativ DNEL 700 mg/m³ (Arbeiter)
 Kurzzeit-Exposition - lokale Effekte:
 Inhalativ DNEL 700 mg/m³ (Arbeiter)
 Aceton, CAS 67-64-1
 dermal Langzeit (chronisch) systemisch: 186 mg/kg/Tag
 inhalativ Kurzzeit (akut) lokal: 2420 mg/m³
 inhalativ Kurzzeit (akut) systemisch: 1210 mg/m³

- **PNECs**

Ethylacetat 141-78-6
 Wasser Süßwasser: 0,26 mg/l
 Wasser Meerwasser: 0,026 mg/l
 Wasser Aqua intermittent: 1,65 mg/l
 Wasser Süßwasser Sediment: 1,25 mg/kg
 Wasser Meerwasser Sediment: 0,125 mg/kg
 Boden - 0,24 mg/kg
 Kläranlage (STP) - 650 mg/l
 Sekundärvergiftung - 200 mg/kg
 Cyclohexan CAS 110-82-7
 PNEC 2,99 mg/kg (Boden)
 3,24 mg/l (Kläranlagen)
 0,207 mg/l (Meerwasser)
 3,627 mg/kg (Süßwassersediment)
 0,207 mg/l (Süßwasser)
 0,207 mg/l (sporadische Freisetzung)
 Aceton, CAS 67-64-1
 Wasser Süßwasser: 10,6 mg/l
 Wasser Meerwasser: 1,06 mg/l
 Wasser Aqua intermittent: 21 mg/l
 Wasser Süßwasser Sediment: 30,4 mg/kg
 Wasser Meerwasser Sediment: 3,04 mg/kg
 Boden - :29,5 mg/kg
 Kläranlage (STP) -: 100 mg/l

- **Additional information:** The lists that were valid during the compilation were used as basis.

- **8.2 Exposure controls**

- **Personal protective equipment**

- **General protective and hygienic measures**

The usual precautionary measures should be adhered to general rules for handling chemicals.

Keep away from foodstuffs, beverages and food.

Take off immediately all contaminated clothing

Wash hands during breaks and at the end of the work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- **Breathing equipment:**

Use breathing protection in case of insufficient ventilation.



In case of brief exposure or low pollution use breathing filter apparatus. In case of intensive or longer exposure use breathing apparatus that is independent of circulating air.

- **Recommended filter device for short term use:** Filter AX

(Contd. on page 6)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.09.2015

Version number 2

Revision: 04.09.2015

Trade name: **CONTI SECUR BFA WEISS**

(Contd. of page 5)

- **Protection of hands:**



Protective gloves.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Solvent resistant gloves

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Butyl rubber, BR

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed safety glasses.

- **Body protection:** Protective work clothing.

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Fluid

Colour: According to product specification

- **Odour:** Characteristic

- **Odour threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range: Not determined

Boiling point/Boiling range: 56 °C (DIN 53171)

- **Flash point:** -20 °C (DIN 53213)

- **Inflammability (solid, gaseous)** Not applicable.

- **Ignition temperature:**

Decomposition temperature: Not determined.

- **Self-inflammability:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/steam mixtures is possible.

- **Critical values for explosion:**

Lower: 0.7 Vol % (EN 1839)

(Contd. on page 7)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.09.2015

Version number 2

Revision: 04.09.2015

Trade name: **CONTI SECUR BFA WEISS**

(Contd. of page 6)

Upper:	13.0 Vol % (EN 1839)
· Vapour pressure at 20 °C:	233 hPa (DIN 51640)
· Density at 20 °C	ca. 0.86 g/cm ³ (DIN 51757)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
dynamic:	Not determined.
kinematic at 20 °C:	ca. 151 s (ISO 4 mm)
· Solvent content:	
Organic solvents:	76.4 %
Solids content:	23.6 % (ISO 3251)
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **10.3 Possibility of hazardous reactions** Develops readily flammable gases / fumes
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**

- **LD/LC50 values that are relevant for classification:**

141-78-6 ethyl acetate

Oral	LD50	5620 mg/kg (rat)
Inhalative	LC50/4h	11.72 mg/kg (rat)

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rbt)
Inhalative	LC50/4h	76 mg/kg (rat)

1314-13-2 zinc oxide

Oral	LD50	> 5000 mg/kg (rat)
------	------	--------------------

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.

(Contd. on page 8)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.09.2015

Version number 2

Revision: 04.09.2015

Trade name: CONTI SECUR BFA WEISS

(Contd. of page 7)

- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause drowsiness or dizziness.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

141-78-6 ethyl acetate

EC50/48h	717 mg/l (Daphnia magna)
IC50/48h	3300 mg/l (Desmodesmus subspicatus)
LC50/96h	230 mg/l (Pimephales promelas)

67-64-1 acetone

EC50/48h	12600 - 12700 mg/l (Daphnia magna)
LC50/96h	8300 mg/l (Lepomis macrochirus)

1314-13-2 zinc oxide

EC50/48h	2.2 mg/l (Daphnia magna)
----------	--------------------------

· 12.2 Persistence and degradability

141-78-6 ethyl acetate

Bio.Abbaubark./28 d	100 % (-)
---------------------	-----------

67-64-1 acetone

Bio.Abbaubark./28 d	91 % (-)
---------------------	----------

· 12.3 Bioaccumulative potential

 No further relevant information available.

· 12.4 Mobility in soil

 No further relevant information available.

· Ecotoxicological effects:

· Remark:

 Toxic for fish

· Additional ecological information:

· General notes:

Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms

· 12.5 Results of PBT and vPvB assessment

· PBT:

 Not applicable.

· vPvB:

 Not applicable.

· 12.6 Other adverse effects

 No further relevant information available.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 9)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.09.2015

Version number 2

Revision: 04.09.2015

Trade name: **CONTI SECUR BFA WEISS**

(Contd. of page 8)

Must be specially treated under adherence to official regulations.

- **European waste catalogue**

08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 04 00	wastes from MFSU of adhesives and sealants (including waterproofing products)
08 04 09*	waste adhesives and sealants containing organic solvents or other dangerous substances

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**

- **ADR, IMDG, IATA**

UN1133

- **14.2 UN proper shipping name**

- **ADR**

1133 ADHESIVES, ENVIRONMENTALLY HAZARDOUS, special provision 640D

- **IMDG**

ADHESIVES (Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane (*), zinc oxide), MARINE POLLUTANT

- **IATA**

ADHESIVES

- **14.3 Transport hazard class(es)**

- **ADR, IMDG**



- **Class**

3 Flammable liquids.

- **Label**

3

- **IATA**



- **Class**

3 Flammable liquids.

- **Label**

3

- **14.4 Packing group**

- **ADR, IMDG, IATA**

II

- **14.5 Environmental hazards:**

Product contains environmentally hazardous substances: zinc oxide, Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane (*)

- **Marine pollutant:**

Yes

- **Special marking (ADR):**

Symbol (fish and tree)

Symbol (fish and tree)

- **14.6 Special precautions for user**

Warning: Flammable liquids.

- **Kemler Number:**

33

(Contd. on page 10)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.09.2015

Version number 2

Revision: 04.09.2015

Trade name: **CONTI SECUR BFA WEISS**

(Contd. of page 9)

- | | |
|--|---|
| · EMS Number: | F-E,S-E |
| · 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code | Not applicable. |
| · Transport/Additional information: | |
| · ADR | |
| · Limited quantities (LQ) | 5L |
| · Transport category | 2 |
| · Tunnel restriction code | D/E |
| · UN "Model Regulation": | UN1133, ADHESIVES, special provision 640D, ENVIRONMENTALLY HAZARDOUS, 3, II |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **National regulations**
- **Technical instructions (air):**

Class	Share in %
NK	25-50
- **Water hazard class:**
- **VOC (EU) %** 79.49 %
- **Code MAL** 5-3
- **VOC (EU)** 683.6 g/l
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

SECTION 16: Other information

These data are based on our present knowledge. However, they shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
 - H224 Extremely flammable liquid and vapour.
 - H225 Highly flammable liquid and vapour.
 - H304 May be fatal if swallowed and enters airways.
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H319 Causes serious eye irritation.
 - H336 May cause drowsiness or dizziness.
 - H361f Suspected of damaging fertility.
 - H373 May cause damage to organs through prolonged or repeated exposure.
 - H400 Very toxic to aquatic life.
 - H410 Very toxic to aquatic life with long lasting effects.
 - H411 Toxic to aquatic life with long lasting effects.
- **Abbreviations and acronyms:**
 - ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 - IMDG: International Maritime Code for Dangerous Goods
 - IATA: International Air Transport Association
 - GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 - EINECS: European Inventory of Existing Commercial Chemical Substances

(Contd. on page 11)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.09.2015

Version number 2

Revision: 04.09.2015

Trade name: CONTI SECUR BFA WEISS

(Contd. of page 10)

ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 1: Flammable liquids, Hazard Category 1
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Repr. 2: Reproductive toxicity, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2
Asp. Tox. 1: Aspiration hazard, Hazard Category 1
Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 1
Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1
Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2

*** Data compared to the previous version altered.**

GB

(Contd. on page 12)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.09.2015

Version number 2

Revision: 04.09.2015

Trade name: **CONTI SECUR BFA WEISS**

(Contd. of page 11)

Annex: Exposure scenario 1

- **Short title of the exposure scenario**
ETHYL ACETATE (CAS141-78-6)
PROFESSIONAL AND INDUSTRIAL USE OF ADHESIVES
- **Sector of Use** SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- **Product category** PC1 Adhesives, sealants
- **Process category**
 - PROC1 Use in closed process, no likelihood of exposure
 - PROC2 Use in closed, continuous process with occasional controlled exposure
 - PROC3 Use in closed batch process (synthesis or formulation)
 - PROC4 Use in batch and other process (synthesis) where opportunity for exposure arises
 - PROC5 Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)
 - PROC8a Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities
 - PROC8b Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
 - PROC9 Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
- **Environmental release category** ERC2 Formulation of preparations
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use** Customary application according to section 1.
- **Duration and frequency** 5 workdays/week.
- **Physical parameters**
The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.
- **Physical state** Fluid
- **Concentration of the substance in the mixture** Raw material.
- **Other operational conditions** Observe the normal safety regulations when handling chemicals
- **Other operational conditions affecting environmental exposure** No special measures required.
- **Other operational conditions affecting worker exposure**
Avoid contact with eyes.
Take precautionary measures against static discharge.
Keep away from sources of ignition - No smoking.
- **Other operational conditions affecting consumer exposure** Keep out of the reach of children.
- **Other operational conditions affecting consumer exposure during the use of the product**
Not applicable.
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures** No special measures required.
- **Technical protective measures**
Provide explosion-proof electrical equipment.
Ensure that suitable extractors are available on processing machines
- **Personal protective measures**
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes.
Tightly sealed safety glasses.
Protective gloves.
- **Measures for consumer protection**
Ensure adequate labelling.
Keep locked up and out of the reach of children.

(Contd. on page 13)

GB

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.09.2015

Version number 2

Revision: 04.09.2015

Trade name: CONTI SECUR BFA WEISS

(Contd. of page 12)

- **Environmental protection measures**
- **Water** No special measures required.
- **Disposal measures** Disposal must be made according to official regulations.
- **Disposal procedures**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Waste type** Partially emptied and uncleaned packaging
- **Exposure estimation**
- **Consumer** Not relevant for this Exposure Scenario.

GB

(Contd. on page 14)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.09.2015

Version number 2

Revision: 04.09.2015

Trade name: CONTI SECUR BFA WEISS

(Contd. of page 13)

Annex: Exposure scenario 2

- **Short title of the exposure scenario**

Cyclohexane

Industrielle Verwendung von Beschichtungen und Klebstoffen

- **Sector of Use** SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

- **Product category** PC1 Adhesives, sealants

- **Process category**

PROC1 Use in closed process, no likelihood of exposure

PROC2 Use in closed, continuous process with occasional controlled exposure

PROC3 Use in closed batch process (synthesis or formulation)

PROC4 Use in batch and other process (synthesis) where opportunity for exposure arises

PROC5 Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

PROC8a Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9 Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC15 Use as laboratory reagent

- **Environmental release category** ERC3 Formulation in materials

- **Notes** The product is intended for professional use.

- **Description of the activities / processes covered in the Exposure Scenario**

See Section 1 of the Safety Data Sheet

- **Conditions of use** Customary application according to section 1.

- **Duration and frequency** 5 workdays/week.

- **Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- **Physical state** Fluid

- **Concentration of the substance in the mixture** Raw material.

- **Other operational conditions** Observe the normal safety regulations when handling chemicals

- **Other operational conditions affecting environmental exposure**

Observe section 6 of the Safety Data Sheet (Accidental release measures).

- **Other operational conditions affecting worker exposure** Avoid contact with the skin and eyes.

- **Other operational conditions affecting consumer exposure** No special measures required.

- **Risk management measures**

- **Worker protection**

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- **Technical protective measures** Ensure good ventilation/exhaustion at the workplace.

- **Personal protective measures**

The usual precautionary measures should be adhered to general rules for handling chemicals.

- **Environmental protection measures**

Avoid release to the environment. Obtain special instructions / refer to Safety Data Sheet.

- **Disposal measures**

Must not be disposed of with household waste. Do not allow to reach sewage system.

- **Disposal procedures**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Waste type** Partially emptied and uncleaned packaging

- **Exposure estimation**

- **Consumer** Not relevant for this Exposure Scenario.

(Contd. on page 15)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.09.2015

Version number 2

Revision: 04.09.2015

Trade name: CONTI SECUR BFA WEISS

· **Guidance for downstream users** No further relevant information available.

(Contd. of page 14)

GB

(Contd. on page 16)

Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 04.09.2015

Version number 2

Revision: 04.09.2015

Trade name: **CONTI SECUR BFA WEISS**

(Contd. of page 15)

Annex: Exposure scenario 3

- **Short title of the exposure scenario**

ACETONE (CAS 67-64-1)

Industrielle Verwendung von Beschichtungen und Klebstoffen

- **Sector of Use** SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

- **Product category** PC1 Adhesives, sealants

- **Process category**

PROC1 Use in closed process, no likelihood of exposure

PROC2 Use in closed, continuous process with occasional controlled exposure

PROC3 Use in closed batch process (synthesis or formulation)

PROC4 Use in batch and other process (synthesis) where opportunity for exposure arises

PROC5 Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)

PROC7 Industrial spraying

PROC8a Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at non-dedicated facilities

PROC8b Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC9 Transfer of substance or preparation into small containers (dedicated filling line, including weighing)

PROC14 Production of preparations or articles by tableting, compression, extrusion, pelletisation

PROC15 Use as laboratory reagent

- **Environmental release category** ERC3 Formulation in materials

- **Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

- **Conditions of use** Customary application according to section 1.

- **Duration and frequency** 5 workdays/week.

- **Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- **Physical state** Fluid

- **Concentration of the substance in the mixture** Raw material.

- **Other operational conditions**

The usual precautionary measures should be adhered to general rules for handling chemicals.

- **Other operational conditions affecting environmental exposure** No special measures required.

- **Other operational conditions affecting worker exposure**

Avoid contact with eyes.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

- **Other operational conditions affecting consumer exposure** Keep out of the reach of children.

- **Other operational conditions affecting consumer exposure during the use of the product**

Not applicable.

- **Risk management measures**

- **Worker protection**

- **Organisational protective measures** No special measures required.

- **Technical protective measures**

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

- **Personal protective measures**

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Tightly sealed safety glasses.

Protective gloves.

(Contd. on page 17)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 04.09.2015

Version number 2

Revision: 04.09.2015

Trade name: CONTI SECUR BFA WEISS

(Contd. of page 16)

- **Measures for consumer protection**
Ensure adequate labelling.
Keep locked up and out of the reach of children.
- **Environmental protection measures**
- **Water** *No special measures required.*
- **Disposal measures** *Disposal must be made according to official regulations.*
- **Disposal procedures**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Waste type** *Partially emptied and uncleaned packaging*
- **Exposure estimation**
- **Consumer** *Not relevant for this Exposure Scenario.*
- **Guidance for downstream users** *No further relevant information available.*

GB